

FIG 523 - BRASS GEKA TYPE FITTING FEMALE



ITEM CODE	SIZE RANGE	
	BSP	METRIC mm
523/0015	1/2"	15
523/0020	3/4"	20
523/0025	1"	25

MATERIAL
Brass Construction
Rubber Seal

TECHNICAL DATA:

Temperature rating:

0°C to 60°C

Suitable Applications:

Water, Industrial, Suction and Discharge Hoses

Features:

Commonly used onto a male side of a tap for a dragging or hose
Claw action for quick connecting and disconnecting

PERFECT SEALS
PEACE OF MIND
PROVEN DURABILITY

FIG 524 - BRASS GEKA TYPE FITTING MALE



ITEM CODE	SIZE RANGE	
	BSP	METRIC mm
523/0015	1/2"	15
523/0020	3/4"	20
523/0025	1"	25

MATERIAL
Brass Construction
Rubber Seal

TECHNICAL DATA:

Temperature rating:

0°C to 60°C

Suitable Applications:

Water, Industrial, Suction and Discharge Hoses

Features:

Male thread can be attached to any valve or fitting for easy connecting / disconnecting
Claw action for quick connecting and disconnecting

PERFECT SEALS
PEACE OF MIND
PROVEN DURABILITY

FIG 525 - BRASS GEKA TYPE FITTING HOSE TAIL



SIZE RANGE	
ITEM CODE	METRIC mm
523/0013	13
523/0016	16
523/0019	19
523/0025	25

MATERIAL
Brass Construction
Rubber Seal

TECHNICAL DATA:

Temperature rating:

0°C to 60°C

Suitable Applications:

Water, Industrial, Suction and Discharge Hoses

Features:

Hose tail used for draglines and hoses

Claw action for quick connecting and disconnecting

PERFECT SEALS
PEACE OF MIND
PROVEN DURABILITY

FIG 526 - BRASS GEKA TYPE FITTING BLANK



SIZE RANGE	
ITEM CODE	METRIC mm
523/BLANK	BLANK

MATERIAL
Brass Construction
Rubber Seal

TECHNICAL DATA:

Temperature rating:	0°C to 60°C
Suitable Applications:	Water, Industrial, Mortar, Suction and Discharge Hoses
Features:	Easy to fit

PERFECT SEALS
PEACE OF MIND
PROVEN DURABILITY